

LY Prefabricated Connector

Industry signal Power supply

■ Coupling: Thread



Thread

ISO9001



ISO14001



ISO45001





Index

Technical Data	2
Product Application Diagram	3
LY Free Plug Part Number	4
LY Free Receptacle Part Number	5
LY Figures of Shell Size	6
LY Panel Mounted Receptacle Part Number	7
LY Panel Mounted Receptacle Drawings & Dimensions	8
Contacts Arrangement	9-10
IP67 Metal Protective Caps	11
Mounting Plate	12

★ Please contact sales for customization!



High-tech Enterprise Certificate



Foreign Invested Advanced



Enterprise Credit Rating AAA

LY Thread Prefabricated Wire Harness Connector



Environmental

Overvoltage Category	II / III	Frequency	50/60Hz
Relative Humidity	95% at 40°C ± 2°C		
Salty Spray Corrosion	≥96h	IEC60512-11-7	
Protection Degree	IP65/IP67	IEC60529	
Degree of Pollution	2/3		
Flame Resistance	UL94V-0		
Liquid Resistance	Oil, Mineral oil, Acid, Alkali		

Material: RoHS

Shell	Copper alloy (Plating Ni-Cr)
Contact	Brass (Silver) Gold plating, customize
Insert	Plastic UL Certificate
	CTI ≥ 600V
	Plastic UL Certificate

Mechanical Features


Vibration	10-500Hz 5g<1μs	IEC60512-6d
Shock	50g 11ms	IEC60512-6C
Mechanical Life	≥500	IEC60512-9-1

Electric Features

Operating Temperature	Lower limit-55°C; Upper limit+125°C				
Insulation Resistance	Normal ≥ 5000MΩ; Damp Heat ≥ 100MΩ				
Diameter of Contacts (mm)	0.8	1.0	1.5	1.6	2.5
Rated Current (A)	3A	5A	10A	13A	20A
Rated Voltage (VAC)	See Contacts Arrangement ⑨ ~ ⑩				
Wire Gauge (mm²)	< 0.3	0.5~0.75	1~1.5	1~2	1.5~2.5
Contact Resistance (mΩ)	< 8	< 5	< 2.5	< 2.25	< 1
Withstand Voltage (VAC) [50/60Hz]	See Contacts Arrangement ⑨ ~ ⑩ Remark: For High Altitude Low Pressure Environment, Refer to GB/T4797.2-2005				
Screen	According to customer requirements				

Product Application Diagram

FH Receptacle



LY Free Plug — Part Number — (Explanation)

Single Free Plug

e.g. **LY** **12** **J4** **T** **P** **D****


① ② ③ ④ ⑤ ⑥



Double Free Plug

e.g. **LY** **12** **J4** **T** **F** **S**** // **LY** **12** **K4** **W**

① ② ③ ④ ⑤ ⑥ // ⑦ ⑧ ⑨ ⑩



Explanation

① ⑦ **LY**
Thread Prefabricated

② ⑧ **12,16,18** : Shell Spec. See Page 11-12

③ ⑨ Insert:
J or **K** **4**
J: Pin
K: Socket
Contacts

Insert Spec. See Page 11-12

④ ⑩ **T** : Straight Free Plug
W : 90° Angled Free Plug

⑤ **P** : Shield
F : Unshielded

⑥ **D** or **S** ******
D: Single twisted cable
S: Twisted pair cable
Cable length

LY Free Receptacle — Part Number — (Explanation)

Single Free Receptacle

e.g. LY 12 J5 ZT P D**

① ② ③ ④ ⑤ ⑥

Customize




Double Free Receptacle

e.g. LY 12 J4 ZT F S** // LY 12 K4 ZW

① ② ③ ④ ⑤ ⑥ // ⑦ ⑧ ⑨ ⑩

Customize



Explanation

① ⑦ LY

Thread Prefabricated

② ⑧ 12,16,18 : Shell Spec. See Page 11-12

③ ⑨ Insert:

J K 4

J: Pin K: Socket

Contacts

Insert Spec. See Page 11-12

④ ⑩ ZT : Straight Free Receptacle

ZW : 90° Angled Free Receptacle

⑤ P : Shield

F : Unshielded

⑥ D OR S **


D: Single twisted cable

S: Twisted pair cable

Cable length

LY Figures of Shell Size


T Straight Free Plug



Free Plug-Straight



ZT Straight Free Receptacle




Free Receptacle-Straight



Unit: mm

Spec.	A I (max)	A II (max)	B
12	50	56	φ 17
16	56	62	φ 22
18	62	64	φ 24.5


W 90° Angled Plug



Free Plug-90° Angled



ZW 90° Angled Receptacle



Free Receptacle-90° Angled




Unit: mm

Spec.	A	B	L max
12	45	φ 17	45
16	50	φ 22	50
18	52.5	φ 24.5	52.5

LY Panel Mounted Receptacle — Part Number — (Explanation)

e.g. **LY** **12** **K4** **Z**

① ② ③ ④



Explanation

① **LY**
Thread Prefabricated

③ Insert:
J or K 4
J: Pin
K: Socket
Contacts

Insert Spec. See Page 11-12

② **12,16,18** : Shell Spec. See Page 11-12

④ **Z** : Panel Mounted Receptacle

LY Order code for three-way adapter





Product Spec.	Order Code
LY12	LY12-3T
LY16	LY16-3T
LY18	LY18-3T

LY Panel Mounted Receptacle Drawings & Dimensions






LY Thread



Unit: mm

Spec.	A	C	E	F	G	H
LY12-Z	20	φ12	11.5	14±0.1	19	4-φ2.3
LY16-Z	20	φ16	12	20±0.1	26	4-φ3.2
LY18-Z	20	φ18	12	22±0.1	28	4-φ3.2

Mounting Hole Dimensions













Receptacle Mounting Hole Data








Unit: mm

Spec.	F	J	H	L (min)	4×S Screw
LY12-Z	14±0.1	φ12.2	4-φ2.3	28	M2
LY16-Z	20±0.1	φ16.3	4-φ3.2	36	M3
LY18-Z	22±0.1	φ18.3	4-φ3.2	38	

Contacts Arrangement














View from mating face









Shell Spec.	12					
J Contacts	J2	J3	J4	J5	J6	J7
J : Pin 						
K Contacts	K2	K3	K4	K5	K6	K7
K : Socket 						
Contact Diameter×Qty.	φ 1.6 × 2	φ 1.0 × 3	φ 1.0 × 4	φ 1.0 × 5	φ 1.0 × 6	φ 1.0 × 7
Rated Current	13A	5A	5A	5A	5A	5A
Rated Voltage	250V	160V	100V	63V	32V	32V
Withstand Voltage(50/60Hz)	1390V	1000V	840V	840V	500V	500V
Wire Gauge	1~2mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²

Shell Spec.	16					
J Contacts	J2	J2a	J3	J3a	J3b	J4
J : Pin 						
K Contacts	K2	K2a	K3	K3a	K3b	K4
K : Socket 						
Contact Diameter×Qty.	φ 1.5 × 2	φ 2.5 × 2	φ 1.0 × 3	φ 1.5 × 3	φ 2.5 × 3	φ 1.0 × 4
Rated Current	10A	20A	5A	10A	20A	5A
Rated Voltage	250V	200V	250V	250V	200V	250V
Withstand Voltage(50/60Hz)	1500V	1000V	1000V	1500V	1500V	1000V
Wire Gauge	1~1.5mm ²	1.5~2.5mm ²	0.5~0.75mm ²	1~1.5mm ²	1.5~2.5mm ²	0.5~0.75mm ²

Contacts Arrangement


View from mating face

Shell Spec.		16						
J	Contacts	J4a	J5	J7	J8	J9	J10	J12
 J: Pin								
K	Contacts	K4a	K5	K7	K8	K9	K10	K12
 K: Socket								
Contact Diameter×Qty.		φ1.5×4	φ1.0×5	φ1.0×7	φ1.0×8	φ1.0×9	φ1.0×10	φ1.0×12
Rated Current		10A	5A	5A	5A	5A	5A	5A
Rated Voltage		200V	125V	80V	80V	50V	50V	32V
Withstand Voltage (50/60Hz)		1000V	1000V	840V	500V	840V	840V	370V
Wire Gauge		1~1.5mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²	0.5~0.75mm ²

Shell Spec.		18				
J	Contacts	J3	J6	J8	J14	
 J: Pin						
K	Contacts	K3	K6	K8	K14	
 K: Socket						
Contact Diameter×Qty.		φ2.5×3	φ1.6×6	φ1.6×3	φ1.0×5	φ1.0×14
Rated Current		20A	13A	13A	5A	5A
Rated Voltage		250V	160V	160V		100V
Withstand Voltage (50/60Hz)		1500V	840V	840V		840V
Wire Gauge		1.5~2.5mm ²	1~2mm ²	1~2mm ²	0.5~0.75mm ²	0.5~0.75mm ²

IP67 Metal Protective Caps

Free Plug Cap




(b)

Unit: mm

Free Plug Cap Order Code	D	L
LY12-CG	17	17.3
LY16-CG	22	17.3
LY18-CG	24.5	17.3

Free Receptacle Cap




(b)

Unit: mm

Free Receptacle Cap Order Code	D	L
LY12-LG	18.3	14.8
LY16-LG	23.5	16.3
LY18-LG	25.4	16.3

Panel Mounted Receptacle Cap




(b)

Unit: mm

Receptacle Cap Order Code	D	L
LY12-FG	18.3	14.8
LY16-FG	23.5	16.3
LY18-FG	25.4	16.3

Mounting Plate




Technical advantages: (1) Convenient and Fast (2) Firm, Resistance to shock and vibration



◆ Front Mounting



Mounting Plate Order Code, Size



Unit: mm

Order Code	Shell Size	R	S	H	Thread M	Screw Spec
12D	12	14.00	19.00	2.60	M2	M2 x 10
16D	16	20.00	26.00		M3	M3 x 10
18D	18	22.00	28.00			



SHANGHAI HUALUN INSTRUMENTS & ELECTRONICS CO., LTD.
上海华伦仪表电子有限公司

SALES & MARKETING DEPARTMENT

市场销售部

地址: 上海天目西路218号嘉里不夜城2座3409室
ADD: Rm3409, Tower2, Kerry Everbright City, West
Tianmu Rd218, Shanghai

邮编(P.C.): 200070

电话(TEL): 86-21-63178300 63178586 63177566

传真(FAX): 86-21-63178083

电邮(E-MAIL): sales@hualun.sh.cn
sales@hualunconnector.com

网址(WEB): www.hualun.sh.cn
www.华伦连接器.com
www.hualunconnector.com
www.hualunconnectors.com

FACTORY & HEADQUARTERS

工厂本部

地址: 上海千阳路271号(金江工业园) 1、3号厂房
ADD: Factory building 1 & 3, Jinjiang Industrial
Park, Qianyang Rd271, Shanghai

邮编(P.C.): 200333

- Hualun reserves the right to modify the technical and upgrade of the product
- Any form of diversion of this catalogue must be authorized by Hualun